

Technical Data Sheet.

Permahyd[®] Cleaning of equipment and spray guns

This product is for professional painting of vehicles only.



VR Technical Data Sheet No.905.0(01/12/2000) Jan. 2007

Copyright© 2007 Dupont. Spies Hecker[®], Raderal[®], Permacron[®], Permahyd[®], Permasolid[®], Priomat[®], and Permanent[®] are registered trademarks of E.I. du Pont de Nemours and Company for its brands of performance coating materials. All rights reserved.

Forward

If, when cleaning equipment and spray guns, waste disposal is taken into consideration and priority given to avoiding waste, the use of water-borne products can reduce costs.

Since Spies Hecker water-borne products can be mixed at any ratio with Permahyd® VE Water 6000. It later can be used for cleaning spray guns and equipment provided the spray guns are carefully emptied after use. They can be cleaned with Demineralized water in the spray booth without causing measurable pollution or producing contaminated cleaning agents.

Water contaminated by cleaning other utensils can be used to rinse out used spray guns and also be sprayed. Sticking, dried water-borne paint residues are removed with conventional cleaning agents in spray gun cleaners.

I. Cleaning spray guns

1. Empty gun carefully.
2. Clean gun with Permahyd® VE Water 6000.
3. Spray contaminated water in the spray booth.
4. Remove sticking, dried water-borne paint residues with a Cleaning Thinner.
5. After cleaning or prior to further use, rinse gun with Permahyd® VE Water 6000.

II. Cleaning other equipment (stirring sticks, measuring sticks, mixing containers)

1. Remove wet deposits with Permahyd® VE Water 6000.
2. Remove sticking, dried water-borne paint residues with a Cleaning Thinner.

Important note:

Contaminated Demineralized water must never be mixed with contaminated conventional cleaning agents, as this makes disposal difficult and therefore more expensive, if not impossible.

Important Regulatory Information

- **For industrial use only by professional, trained painters. Not for sale to or use by the general public. Before using, read and follow all label and MSDS precautions. If mixed with other components, mixture will have hazards of all components. Do not sand, flame cut, braze or weld dry coating without a NIOSH approved air purifying respirator with particulate filters or appropriate ventilation, and gloves.**
- Any analytical results set forth herein do not constitute a warranty of specific product features or of the product's suitability for a specific purpose. All products are sold pursuant to our general conditions of sale. We hereby disclaim all warranties and representations, express or implied, with respect to this product, including any warranty of merchantability or fitness for a particular purpose. This product is protected by patent law, trademark law, copyright law, international treaties and/or other applicable law. All rights reserved. Unauthorized sale, manufacturing or use may result in civil and criminal penalties.

SPIES HECKER
47818 West Anchor Court
Plymouth, MI 48170
Tel. 888-371-3313
Fax 734-354-3407

